


Painted self closing gate SGEUFHPC2





link to the product:

 $\frac{\text{https://tubefittings.eu/en/self-closing-safety-gates/5012-painted-self-closing-gate-sgeufhpc2-590}{7291151716.\text{html}}$

Price: **€1,265.00** gross

Manufacturer: Kee Safety

Referention number: SGEUFH1PC

Information:

The Kee Gate® self-closing safety gate is a professional solution for protecting edges, entrances, and passages in high-risk areas. Equipped with a spring-loaded self-closing mechanism, it automatically shuts after use, eliminating the risk of leaving openings and enhancing worker safety. Its durable galvanized steel construction, also available in high-visibility yellow or RAL colors, ensures corrosion resistance and long-lasting performance even in harsh industrial environments. With adjustable width and easy installation, Kee Gate® gates are available in single, double, and full-height versions – perfectly fitting various openings. The product is CE certified and compliant with PN-EN and OSHA standards, ensuring reliability and international safety standards. It is an effective, flexible, and durable protection solution that combines top-level safety with ease of use.

Expand description []

Product features

| Production Standard compliant with working at height regulations, meet the requirements of EN 14122-3:2016 and EN 13374 standards, and conform to OSHA standards. Mounting method Reversible hinges (left/right) and adjustable width Product Self-Closing Gate Recommended use External and internal Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Length | 110 cm |
|---|---------------------|---|
| Production Standard Kee Gate safety gates are CE accredited in accordance with PN EN 1090 compliant with working at height regulations, meet the requirements of EN 14122-3:2016 and EN 13374 standards, and conform to OSHA standards. Mounting method Reversible hinges (left/right) and adjustable width Product Self-Closing Gate Recommended use External and internal Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Width | 100 cm |
| Production Standard compliant with working at height regulations, meet the requirements of EN 14122-3:2016 and EN 13374 standards, and conform to OSHA standards. Mounting method Reversible hinges (left/right) and adjustable width Product Self-Closing Gate Recommended use External and internal Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Colour | Yellow |
| Product Self-Closing Gate Recommended use External and internal Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Production Standard | EN 14122-3:2016 and EN 13374 standards, and conform to OSHA |
| Recommended use External and internal Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Mounting method | Reversible hinges (left/right) and adjustable width |
| Finish Powder-coated Self-closing mechanism eliminates the need for springs or electrical | Product | Self-Closing Gate |
| Self-closing mechanism eliminates the need for springs or electrical | Recommended use | External and internal |
| Properties Self-closing mechanism eliminates the need for springs or electrical | Finish | Powder-coated |
| components | Properties | , , |

3-10-2025