



## Mini crossover platform with 200mm clearance

Długość:



link to the product:

https://tubefittings.eu/en/roof-access/5034-mini-crossover-platform-with-200mm-clearance.html

Price: **€410.00** gross

Manufacturer: Kee Safety

Referention number: STMFX2

## Other product combinations:

Długość	gross price
553 mm	€410.00
803 mm	€434.00
1053 mm	€486.00

## Information:

Kee Step® roof access platform is a professional solution providing a safe and stable roof step over platform in any conditions. Anti-slip steps and guardrails minimize accident risks, while the modular structure allows easy adaptation to different roofs and obstacles. The system is available in freestanding, anchored, and custom sizes, ensuring full installation flexibility. Assembly is quick, without welding or roof penetration, preserving roof integrity. Kee Step® meets strict PN-EN, OSHA, and safety standards, ensuring maximum work-at-height safety. It is the ideal freestanding crossover platform and roof access platform for industry, construction, and commercial facilities.

Expand description  $\ \square$ 

## **Product features**

Width480 mmTÜVTÜV certifiedConstruction typeFixed constructionProduction StandardPN EN 516 : 2016 Klasa 1-C, OSHA 1910.23(e)(1)(iii), OSHA 1910.25(b)(3), OSHA 1910.23(c)(2-4), OSHA 1910.23(e)(1)(vi)ProductRoof HatchRecommended useSafe Passage over Low ObstaclesHeight275 mmAnti-slipYes	Material	Steel
Construction type Fixed construction  Production Standard PN EN 516: 2016 Klasa 1-C, OSHA 1910.23(e)(1)(iii), OSHA 1910.25(b)(3), OSHA 1910.23(c)(2-4), OSHA 1910.23(e)(1)(vi)  Product Recommended use Safe Passage over Low Obstacles  Height 275 mm	Width	480 mm
Production Standard PN EN 516 : 2016 Klasa 1-C, OSHA 1910.23(e)(1)(iii), OSHA 1910.25(b)(3), OSHA 1910.23(c)(2-4), OSHA 1910.23(e)(1)(vi)  Product Recommended use Safe Passage over Low Obstacles  Height 275 mm	TÜV	TÜV certified
Production Standard 1910.25(b)(3), OSHA 1910.23(c)(2-4), OSHA 1910.23(e)(1)(vi)  Product Roof Hatch  Recommended use Safe Passage over Low Obstacles  Height 275 mm	Construction type	Fixed construction
Recommended use Safe Passage over Low Obstacles Height 275 mm	Production Standard	
Height 275 mm	Product	Roof Hatch
	Recommended use	Safe Passage over Low Obstacles
Anti-slip Yes	Height	275 mm
	Anti-slip	Yes

4-10-2025